



MODULAR 3D CORK WALL TILES TECHNICAL SPECIFICATION

GENERAL DEFINITION AND PRODUCT COMPOSITION		
Description	Solid agglomerated cork tiles, to be used as interior wallcovering, in accordance with EN 12781. Tiles are shaped by CNC machining (3 different designs), cut in the dimensions of 580x580 mm and have a thickness of 7 mm. The surface is finished with a waterbased protector for increased water and stain resistance.	
Dimensions	580 x 580 x 7 mm	
Finish	CORKGUARD® Aqueous dispersion based on SCOTCHGARD™ and a combination of resins, designed to provide excellent water, oil and stain repellent properties on natural cork. With CleanSurface powered by Microban® antimicrobial technology.	
Product structure		
	Finish: CORKGUARD® (clear or coloured). Core: CNC machined agglomerated cork (natural or toasted).	
Installation	Glued, according to installation instructions.	
TECHNICAL DATA		
Length and width	EN ISO 24342	580 x 580 mm ± 0.5 %
Overall thickness	ISO 7322	7 mm ± 0.2 mm
Squareness Straightness	EN ISO 24342	< 0.4 mm < 0.3 mm
Apparent density	ISO 7322	290 Kg/m ³
Mass per unit area	EN ISO 23997	2000 g/m ² ± 10 %
Tensile strength	ISO 7322	> 1000 kPa



DELIVERING NATURE

MODULAR
3D CORK WALL TILES
TECHNICAL SPECIFICATION

TECHNICAL DATA		
Compression Recuperation	ISO 7322	< 40 % > 80 %
Dimensional variation	EN ISO 23999	< 0.4 %
Moisture content	EN 12105	< 8 %
Curling	EN ISO 23999	< 6 mm
Reaction to fire	EN ISO 11925-2 EN 13501-1	Extent of flame < 150 mm. No flaming droplets. Fire class E
Formaldehyde release	EN 12149	Fulfilled. No formaldehyde-containing materials are added during production.
Release of vinyl chloride monomer (VCM)	EN 12149	Fulfilled. Below Detection Limit
Heavy metals and specific elements Arsenic; Barium; Cadmium; Chromium; Mercury; Lead; Antimony; Selenium	EN 12149	Fulfilled None of these substances are added or have come in direct contact with the product during the manufacturing process
Weighted sound absorption coefficient	EN ISO 354	$\alpha_w = 0.05$
Thermal resistance Thermal conductivity	EN 12667	0.14 (m ² .K)/W 0.05 W/(m.K)
VOC emission	ISO 16000 parts 3, 6, 9	Fulfilled AgBB scheme Fulfilled French Classification A+
GENERAL DATA		
Features	Safe and easy to handle and install; Effective reduction of airborne sound; Increases the thermal comfort; Persistence of characteristics along time; Without the release of toxic gases when burning; Lightweight, flexible and odourless; No harmful chemicals; Natural, biodegradable and recyclable product;	
Packaging	Tiles are packed in cardboard cartons, each containing 21 tiles, providing suitable protection for normal transport and storage conditions. Cartons are identified by a label and/or inkjet printing and palletized. Each pallet is over strapped and wrapped with stretch film. Tiles per carton: 21 (11 tiles D1; 5 tiles D2; 5 tiles D3) Sqm per carton: 7.06 m ² Weight per carton: 14 Kg Cartons per pallet: 24 Sqm per pallet: 169.5 m ²	



DELIVERING NATURE

MODULAR 3D CORK WALL TILES TECHNICAL SPECIFICATION

GENERAL DATA

Limited warranty

We certify that the product is free from manufacturing and structural defects and will remain free of these defects.

Environment

The use of a natural and renewable raw-material and the possibility of total recycling of the product, make MODULAR a reference in terms of ecology and environmental sustainability.
MODULAR tiles composition is more than 90% natural cork, all coming from recycling post-industrial cork by-products.
It contains no PVC and no softeners or other substances hazardous to health or the environment.



FSC® certified products are available upon request

GRANORTE reserves the right to make changes to material and structure to improve the quality or technical performance.